



TL-R1200S-RP

| | |
|---|--|
| Drive Bay | 12 x 3.5-inch SATA 6Gb/s, 3Gb/s |
| Drive Compatibility | 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives |
| Audio Alert On/Off Switch | Yes |
| Form Factor | 2U Rackmount |
| Host Interface | 3 x SFF-8088 |
| LED Indicators | HDD 1-12, Status, Link, Fan error |
| Buttons | Power switch |
| Dimensions (HxWxD) | 88.6 × 482 × 562.5 mm |
| Weight (Net) | 9.49 kg |
| Weight (Gross) | 12.77 kg |
| Max. number of HDDs/SSDs supported | 12 |
| Hard Drive Type | 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | 250W(x2) PSU, 100 - 240V |
| Power Consumption: Operating Mode, Typical | 73.7 W |
| Fan Mode Switch | Yes (Auto, high, medium, low) |
| Fan | 2 x 70mm, 12VDC |

| | |
|--------------------------|--------|
| System Warning | Buzzer |
| Kensington Security Slot | Yes |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.