



TS-873AeU-RP-4G

CPU	AMD Ryzen™ Embedded V1500B 4-core/8-thread 2.2 GHz processor
CPU Architecture	64-bit x86
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
Hardware-accelerated Transcoding	Optional via a PCIe graphics card
System Memory	4 GB SODIMM DDR4 (1 x 4 GB)
Maximum Memory	64 GB (2 x 32 GB)
Memory Slot	2 x SODIMM DDR4 Support ECC memory
Flash Memory	5GB (Dual boot OS protection)
Drive Bay	8 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes
M.2 Slot	2 x M2 2280 (PCIe Gen3 x 1)
SSD Cache Acceleration Support	Yes
GPU pass-through	Yes
2.5 Gigabit Ethernet Port (2.5G/1G/100M)	2 (2.5G/1G/100M/10M)
5 Gigabit Ethernet Port (5G/2.5G/1G/100M)	Optional via a network adapter
10 Gigabit Ethernet Port	Optional via a network adapter
Wake on LAN (WOL)	Yes
Jumbo Frame	Yes

PCIe Slot	1 x PCIe Gen3 x8
USB 3.2 Gen 2 (10Gbps) Port	4 (2 x Type A, 2 x Type C)
HDMI Output	Optional via a PCIe graphics card
Form Factor	2U Rackmount
LED Indicators	HDD 1-8, Status, LAN, USB, Power
Buttons	Power, Reset
Dimensions (HxWxD)	89 × 482 × 297.4 mm
Weight (Net)	8.15 kg
Weight (Gross)	10.92 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	300W PSU(x2), 100 - 240V
Power Consumption: HDD Sleep Mode	32.19 W
Power Consumption: Operating Mode, Typical	58.14 W
Fan	3 x 60mm, 12VDC
System Warning	Buzzer
Standard Warranty	3
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	2000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.