



TS-932PX-4G

| | |
|--|---|
| CPU | AnnapurnaLabs Alpine AL324 ARM® Cortex-A57 4-core 1.7GHz processor |
| CPU Architecture | 64-bit ARM |
| Floating Point Unit | Yes |
| Encryption Engine | Yes |
| System Memory | 4 GB SODIMM DDR4 (1 x 4 GB) |
| Maximum Memory | 16 GB (1 x 16 GB) |
| Memory Slot | 1 x SODIMM DDR4 |
| Flash Memory | 512 MB (Dual boot OS protection) |
| Drive Bay | 5x 3.5-inch+ 4 x 2.5-inch SATA 6Gb/s |
| Drive Compatibility | 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 2.5-inch bays: 2.5-inch solid state drives |
| Hot-swappable | Yes |
| SSD Cache Acceleration Support | Yes |
| 2.5 Gigabit Ethernet Port (2.5G/1G/100M) | 2 (2.5G/1G/100M/10M) |
| 10 Gigabit Ethernet Port | 2 x 10GbE SFP+ |
| Wake on LAN (WOL) | Yes |
| Jumbo Frame | Yes |
| USB 3.2 Gen 1 port | 3 |
| Form Factor | Tower |
| LED Indicators | System Status, LAN, USB, HDD1~5, SSD1-4 |

| | |
|---|--|
| Buttons | Power, Reset, USB Copy |
| Dimensions (HxWxD) | 182.7 × 224.6 × 224.1 mm |
| Weight (Net) | 3.39 kg |
| Weight (Gross) | 4.99 kg |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | External, 120 W, AC 100 to 240 V |
| Power Consumption: HDD Sleep Mode | 23.833 W |
| Power Consumption: Operating Mode, Typical | 43.003 W |
| Fan | 1 x 140mm, 12VDC |
| System Warning | Voice prompts or Buzzer |
| Kensington Security Slot | Yes |
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 700 |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.