



## TS-h1887XU-RP-E2336-32G

**CPU** Intel® Xeon® E-2336 6C 12T 2.9GHz, up to 4.8GHz

**CPU Architecture** 64-bit x86

**Graphic Processors** Optional via a PCIe adapter

**Floating Point Unit** Yes

**Encryption Engine** Yes (AES-NI)

**System Memory** 32 GB ECC DDR4 (2 x 16 GB)

**Maximum Memory** 128GB (4 x 32 GB)

**Memory Slot** 4 x ECC UDIMM DDR4

**Flash Memory** 5GB (Dual boot OS protection)

**Drive Bay** 18 (12 x 3.5-inch SATA + 6 x 2.5-inch SATA)

**Drive Compatibility**

3.5-inch bays:  
3.5-inch SATA hard disk drives  
2.5-inch SATA solid state drives

2.5-inch bays:  
2.5-inch SATA solid state drives

**Hot-swappable** Yes

**M.2 Slot** Optional via a QM2 PCIe adapter

**SSD Cache Acceleration Support** Yes

**GPU pass-through** Yes

**2.5 Gigabit Ethernet Port (2.5G/1G/100M)** 2 (2.5G/1G/100M)

**10 Gigabit Ethernet Port** 2 x 10GBASE-T (10G/5G/2.5G/1G/100M)

**25 Gigabit Ethernet Port** Optional via a PCIe adapter

**Wake on LAN (WOL)** Yes

**PCIe Slot** 3 (2 x Gen4 x4 + 1 x Gen 4 x8)

USB 3.2 Gen 2 (10Gbps) Port	4 x Type-A USB 3.2 Gen 2 5V/1A 10Gbps
HDMI Output	Optional via a PCIe adapter
Form Factor	2U Rackmount
LED Indicators	Status (Green/Red) LAN (Green) USB (Blue) HDD status (Green/Red)
Buttons	Power, Reset
Dimensions (HxWxD)	88.6 × 432 × 511.2 mm
Weight (Net)	13 kg
Weight (Gross)	19 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5~95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	2 x 550W PSU
Power Consumption: HDD Sleep Mode	118.77 W
Power Consumption: Operating Mode, Typical	148.94 W
Fan	4 x 60mm, 12VDC
Standard Warranty	3
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	11000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.