



TDS-h2489FU-4314-1TB (By Request)		
CPU	2 x Intel® Xeon® Silver 4314 16-core/32-thread processor, up to 3.4 GHz	
CPU Architecture	64-bit x86	
Encryption Engine	Yes (AES-NI)	
System Memory	1 TB RDIMM DDR4 ECC (32 x 32 GB)	
Maximum Memory	1 TB (32 x 32 GB)	
Memory Slot	32 x RDIMM DDR4 ECC (16 x slots per socket)	
Flash Memory	5GB (Dual boot OS protection)	
Drive Bay	24 x 2.5-inch	
Drive Compatibility	2.5-inch bays:2.5-inch SATA solid state drives (#17-24)2.5-inch U.2 NVMe PCIe Gen4 x4 solid state drives	
Hot-swappable	Yes	
M.2 Slot	2 Slot 1: M.2 2280 NVMe PCIe Gen 3 x4 or SATA 6Gb/s Slot 2: M.2 2280 NVMe PCIe Gen 3 x2 or SATA 6Gb/s	
SSD Cache Acceleration Support	Yes	
SR-IOV	Yes	
2.5 Gigabit Ethernet Port (2.5G/1G/100M)	4 (2.5G/1G/100M/10M)	
25 Gigabit Ethernet Port	2 x 25GbE SFP28 SmartNIC port	
Wake on LAN (WOL)	Yes	
Jumbo Frame	Yes	
PCIe Slot	2 Slot 1: PCIe Gen4 x16 Slot 2: PCIe Gen4 x8	
USB 3.2 Gen 1 port	4	

Form Factor	Rackmount
LED Indicators	SSD, Status, Power, Fan, Temperaure, Power Module Status, Device Name, IP Address
Buttons	Power, Reset, OLED
Dimensions (HxWxD)	88.3 × 446.2 × 713.2 mm
Weight (Net)	21.31 kg
Weight (Gross)	27.6 kg
Operating Temperature	0 - 35°C (32°F - 95°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	1200W PSU(x2), 100-240Vac Max Wattage: 1200W@200-240Vac 1000W@100-127Vac
Power Consumption: Operating Mode, Typical	467.59 W
Fan	6 x 60mm, 12VDC
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	10,000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.