



TS-133

CPU ARM 4-core Cortex-A55 1.8GHz processor

CPU Architecture 64-bit ARM

Floating Point Unit Yes

Encryption Engine Yes

Neural Processing Unit (NPU) Yes

System Memory 2 GB on board (non-expandable)

Maximum Memory 2 GB on board (non-expandable)

Flash Memory 4 GB (Dual boot OS protection)

Drive Bay 1 x 3.5-inch SATA 6Gb/s, 3Gb/s

Drive Compatibility 3.5-inch SATA hard disk drives
2.5-inch SATA solid state drives

Gigabit Ethernet Port (RJ45) 1

Wake on LAN (WOL) Yes

Jumbo Frame Yes

USB 2.0 port 1

USB 3.2 Gen 1 port 1

Form Factor Tower

LED Indicators System Status, LAN, HDD

Buttons Power, Reset

Dimensions (HxWxD) 187.5 × 66.1 × 157.6 mm

Weight (Net) 0.61 kg

Weight (Gross) 1.27 kg

Operating Temperature 0 - 40 °C (32°F - 104°F)

Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	36W Adapter, 100-240V
Power Consumption: HDD Sleep Mode	2.74 W
Power Consumption: Operating Mode, Typical	7.32 W
Fan	1 x 50mm, 12VDC
System Warning	Buzzer
Standard Warranty	2
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	200

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.