



| TS-h1090FU-7232P-64G | |
|--|---|
| CPU | AMD EPYC™ 7232P/7252 8-core/16-thread processor, up to 3.2 GHz |
| CPU Architecture | 64-bit x86 |
| Encryption Engine | Yes (AES-NI) |
| System Memory | 64 GB RDIMM DDR4 ECC (8 x 8 GB) |
| Maximum Memory | 1 TB+ (12 x 128 GB) |
| Memory Slot | 12 x RDIMM DDR4 |
| Flash Memory | 5GB (Dual boot OS protection) |
| Drive Bay | 10 x 2.5-inch U.2 PCIe NVMe / SATA 6Gbps |
| Drive Compatibility | 2.5-inch U.2 NVMe Gen 4 x4 solid state drives 2.5-inch SATA solid state drives |
| Hot-swappable | Yes |
| SSD Cache Acceleration Support | Yes |
| SR-IOV | Yes |
| 2.5 Gigabit Ethernet Port (2.5G/1G/100M) | 2 (2.5G/1G/100M/10M) |
| 25 Gigabit Ethernet Port | 2 x 25GbE SFP28 SmartNIC port |
| Wake on LAN (WOL) | Yes |
| Jumbo Frame | Yes |
| PCIe Slot | 2 Slot 1: PCIe Gen4 x16 Slot 2: PCIe Gen4 x16 |
| USB 3.2 Gen 1 port | 3 |
| Form Factor | Rackmount |
| LED Indicators | Disk, Status, LAN, storage expansion port status |
| Buttons | Power, Reset |

| Dimensions (HxWxD) | 44 × 430 × 580 mm |
|---|--|
| Weight (Net) | 10.33 kg |
| Weight (Gross) | 13.38 kg |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | 550W PSU (x2), AC 100-240 V |
| Power Consumption: Operating Mode, Typical | 157.97 W |
| Fan | 5 x 60mm, 12VDC |
| System Warning | Buzzer |
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 10,000 |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.