



TS-h3087XU-RP-E2378-64G

CPU Intel® Xeon® E-2378 8C 16T 2.6GHz, up to 4.8GHz

CPU Architecture 64-bit x86

Graphic Processors Optional via a PCIe adapter

Floating Point Unit Yes

Encryption Engine Yes (AES-NI)

System Memory 64 GB ECC DDR4 (4 x 16 GB)

Maximum Memory 128GB (4 x 32 GB)

Memory Slot 4 x ECC UDIMM DDR4

Flash Memory 5GB (Dual boot OS protection)

Drive Bay 30 (24 x 3.5-inch SATA + 6 x 2.5-inch SATA)

Drive Compatibility

- 3.5-inch bays:
- 3.5-inch SATA hard disk drives
- 2.5-inch SATA solid state drives

- 2.5-inch bays:
- 2.5-inch SATA solid state drives

Hot-swappable Yes

M.2 Slot Optional via a QM2 PCIe adapter

SSD Cache Acceleration Support Yes

GPU pass-through Yes

2.5 Gigabit Ethernet Port (2.5G/1G/100M) 2 (2.5G/1G/100M)

10 Gigabit Ethernet Port 2 x 10GBASE-T (10G/5G/2.5G/1G/100M)

25 Gigabit Ethernet Port Optional via a PCIe adapter

Wake on LAN (WOL) Yes

PCIe Slot 3 (2 x Gen4 x4 + 1 x Gen 4 x8)

USB 3.2 Gen 2 (10Gbps) Port	4 x Type-A USB 3.2 Gen 2 5V/1A 10Gbps
HDMI Output	Optional via a PCIe adapter
Form Factor	4U Rackmount
LED Indicators	Status (Green/Red) LAN (Green) USB (Blue) HDD status (Green/Red)
Buttons	Power, Reset
Dimensions (HxWxD)	176.2 × 441.6 × 630.2 mm
Weight (Net)	21.78 kg
Weight (Gross)	29.63 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5~95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	2 x 800W PSU
Power Consumption: HDD Sleep Mode	149.92 W
Power Consumption: Operating Mode, Typical	219.03 W
Fan	4 x 80mm, 12VDC
Standard Warranty	3
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	11000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.