

Branch Model

		AXGATE 40D	AXGATE 50S	AXGATE 80D	AXGATE 90	AXGATE 200
Appearance						
CPU		2 Core	2 Core	2 Core	2 Core	4 Core
Memory		512 MB	512 MB	1 GB	2 GB	2 GB
System Storage		16 GB	16 GB	8 GB	8 GB	8 GB
Log Storage		-	-	-	500 GB	500 GB
Power		Single	Single	Single	Single	Single
NIC	10/100/1000 Base-T	6	14	8	8	6
	1000 Base-X	-	-	-	-	2(Combo)
F/W Throughput (Max)		990 M	990 M	4.5 G	4.7 G	7.3 G
IPS Throughput (Max)		-	-	450 M	450 M	1.6 G
VPN Throughput (Max)		530 M	530 M	1 G	1 G	3.3 G
VPN Tunnel (Max)		5,000	5,000	5,000	10,000	10,000
Concurrent Sessions (Max)		50,000	50,000	300,000	1,000,000	1,000,000
QRNG		-	-	Option	Option	Option
OS		AOS	AOS	AOS	AOS	AOS
Dimensions (WxHxDmm)		260 x 44 x 150	290 x 44 x 180	246 x 44 x 172	316 x 44 x 265	315 x 44 x 260
Weight (Kg)		1.3	1.6	1.3	2.7	2.9

Mid-sized Model

		AXGATE 300S	AXGATE 1300S	AXGATE 2300S
Appearance				
CPU		4 Core	4 Core	8 Core
Memory		4 GB	8 GB	16 GB
System Storage		8 GB	SSD 250 GB	SSD 250 GB
Log Storage		SSD 500 GB	SSD 1 TB	SSD 1 TB
Power		Single	Redundant	Redundant
NIC	10/100/1000 Base-T	8 (Max 12)	8 (Max 16)	8 (Max 16)
	1000 Base-X	Option (Max 4)	4 (Max 8)	4 (Max 8)
	1/10G Combo	-	-	-
	10G Base-R	-	-	Option (Max 2)
F/W Throughput (Max)		12 G	16 G	28 G
IPS Throughput (Max)		3.1 G	3.1 G	5.7 G
VPN Throughput (Max)		3.8 G	3.8 G	6.2 G
VPN Tunnel (Max)		20,000	40,000	50,000
Concurrent Sessions (Max)		2,000,000	5,000,000	9,000,000
QRNG		-	-	-
OS		AOS	AOS	AOS
Dimensions (WxHxDmm)		430 x 44 x 380	430 x 44 x 404	430 x 44 x 404
Weight (kg)		5.5	6.6	6.6

Enterprise Model

	AXGATE 3000	AXGATE 4000S	AXGATE 7000S	AXGATE 13000	AXGATE 13000S
Appearance					
CPU	4 Core	8 Core	16 Core	8 Core x 2	16 Core x 2
Memory	16 GB	32 GB	96 GB	32 GB	96 GB
System Storage	SSD 250 GB	SSD 250 GB	SSD 250 GB	8 GB	SSD 250 GB
Log Storage	SSD 2 TB	SSD 2 TB	SSD 4 TB	4 TB	SSD 4 TB
Power	Redundant	Redundant	Redundant	Redundant	Redundant
NIC	10/100/1000 Base-T	8 (Max 16)	8 (Max 16)	Option (Max 64)	Option (Max 64)
	1000 Base-X	4 (Max 12)	4 (Max 12)	8 (Max 64)	8 (Max 64)
	10G Base-R	Option (Max 4)	Option (Max 4)	4 (Max 32)	4 (Max 32)
	40G Base-R	Option (Max 2)	Option (Max 2)	Option (Max 8)	Option (Max 16)
F/W Throughput (Max)	51 G	50 G	176 G	102 G	320 G
IPS Throughput (Max)	8 G	11.3 G	29.6 G	13.9 G	49.3 G
VPN Throughput (Max)	10 G	14.6 G	25.2 G	18 G	41.7 G
VPN Tunnel (Max)	50,000	50,000	120,000	50,000	120,000
Concurrent Sessions (Max)	9,000,000	25,000,000	60,000,000	25,000,000	60,000,000
QRNG	Option	Option	-	-	Option
OS	AOS	AOS	AOS	AOS	AOS
Dimensions (WxHxDmm)	438 x 88 x 452			438 x 88 x 600	
Weight (kg)	12.6			16	

